Metalmek



595

APPLICAZIONE / APPLICATION

CORRIDOIO PUBBLICO /
PUBLIC CORRIDOR

LOCALE PUBBLICO /
PUBLIC HALL

UFFICIO /
OFFICE






Metalmek


/595 LENS 2095

kg	m³
6.0	0.035


Mounting	
Recessed: installation resting on a 600x600 mm panels of false ceilings with exposed structure.	
Body	
in iron sheet, painted with SOLVENT FREE, epoxy polyester powders, thermosetting at 180°C, after phosphate treatment.	
Light emission	
Direct	
Symmetric	
Optical device	
Darklight lenticular optics, glossy black polycarbonate cells	
Transparent PMMA lens	*Narrow 50°*
	Wide 80°
Light source	
CRI ≥ 80	
Color tollerance: 3 Step MacAdam	
Lifetime: 90000 hours L80B10	
Wiring	
Class Ist	
Feeding 220~240V Ac 50-60 Hz	
Performance data	
Protection rate: IP20	
UGR ≤ 10 (50°) UGR ≤ 16 (80°)	
Regulations	
CEI EN60598-1	
CEI 34-21	
CEI EN 60598-2-2	
Photobiological safety	
EN 62471	
IEC/TR 62778	
Exempt risk – GR 0	
Directives	
2006/95/CE	
2004/108/CE	
UPON REQUEST VERSIONS	
DALI dimmable electonic ballast	
LED CRI ≥ 90	



50° - NARROW



80° - WIDE



Tutte le specifiche tecniche e i dati sono soggetti a modifica in qualsiasi momento e senza preavviso. All technical specifications and datas are subject to modification at any time and without notice.
METALMEK ILLUMINAZIONE S.r.l. Via Ramazzotti, 10 – 20020 Lainate (MI) Italy tel. +39 029373157 – fax +39 02 93710176 – info@metalmek.it – www.metalmek.it

Metalmek

			50°						80°					
	50°		350			500			350			500		
2095 – 595x595	L	K	W	lm*in*	lm*out*	W	lm*in*	lm*out*	W	lm*in*	lm*out*	W	lm*in*	lm*out*
(440)	1x	3000	10,5	1935	1624	15,5	2735	2296	10,5	1935	1676	15,5	2735	2369
		4000		2045	1717		2890	2426		2045	1771		2890	2503

			50°						80°					
	50°		350			500			350			500		
2095 – 595x595	L	K	W	lm*in*	lm*out*	W	lm*in*	lm*out*	W	lm*in*	lm*out*	W	lm*in*	lm*out*
(280)	2x	3000	13,4	2460	1723	19,8	3480	2856	13,4	2460	1763	19,8	3480	2922
		4000		2600	1797		3680	3020		2600	1839		3680	3090

			50°						80°					
	50°		350			500			350			500		
2095 – 595x595	L	K	W	lm*in*	lm*out*	W	lm*in*	lm*out*	W	lm*in*	lm*out*	W	lm*in*	lm*out*
(440)	2x	3000	21	3870	3176	31	5470	4489	21	3870	3249	31	5470	4593
		4000		4090	3357		5780	4743		4090	3434		5780	4853

			50°						80°					
	50°		350			500			350			500		
2095 – 295x1195	L	K	W	lm*in*	lm*out*	W	lm*in*	lm*out*	W	lm*in*	lm*out*	W	lm*in*	lm*out*
(840)	1x	3000	20,1	3690	3097	29,7	5220	4382	20,1	3690	3196	29,7	5220	4522
		4000		3900	3274		5520	4633		3900	3378		5520	4782
	2x	3000	40,2	7380	6195	59,4	10440	8763	40,2	7380	6393	59,4	10440	9044
		4000		7800	6547		11040	9267		7800	6757		11040	9563

Compose the product code according to your needs, following the order indicated in the table below.

ART.	mA	Beam	K	L	L'	Wiring			Color	Row	
2095	**3** *(350)*	**1** *(50°)*	**W** *(3000)*	**0595**	**1** *(280)*	**EO** *(on/off)*	**DD** *(DALI)*	**EM** *(on/off + emergency)*	**B**	**1** *(1x)*	*-SP1*
					2 *(440)*						
	5 *(500)*	**2** *(80°)*	**N** *(4000)*	**1195**	**3** *(840)*				**N**	**2** *(2x)*	

Tutte le specifiche tecniche e i dati sono soggetti a modifica in qualsiasi momento e senza preavviso. All technical specifications and datas are subject to modification at any time and without notice.
METALMEK ILLUMINAZIONE S.r.l. Via Ramazzotti, 10 – 20020 Lainate (MI) Italy tel. +39 029373157 – fax +39 02 93710176 – info@metalmek.it – www.metalmek.it
20230407

FOLLOW US

Metalmek

Metalmek Illuminazione S.r.l.
I - 20045 Lainate (MI)
Via Ramazzotti, 10
Tel. +39 02 9373157
Fax +39 02 9371016
www.metalmek.info
info@metalmek.eu

Metalmek Lighting BV
Canadabaan 7d
NL - 5388 RT Nistelrode
Tel. +31 412 614033
Fax +31 412 613461
www.metalmek.nl
info@metalmek.nl