




2
ANNI DI GARANZIA • YEARS OF GUARANTEE

93101

Code	Nominal lumen	W	CCT	Beam
93101/15/3K	2270	29	3000K	15°
93101/15/4K	2300	29	4000K	15°
93101/28/3K	2270	29	3000K	28°
93101/28/4K	2300	29	4000K	28°
93101/42/3K	2270	29	3000K	42°
93101/42/4K	2300	29	4000K	42°



GRI	15°	28°	42°	DRIVER INCLUDED	IP65	CE	F	⊕	A++	A+	A
85											

Proiettore LED con staffa e picchetto per installazione a pavimento.	LED projector with bracket and ground spike for installation.	Projecteur LED avec étrier et piquet pour installation au sol.	LED-Strahler mit Halterung und Pflock zur Bodeninstallation.
LED CREE	CREE LED	LED CREE	CREE LED
Life time 50.000h (rendimento 70%).	Life time 50.000h (70% lumen maintenance).	Durée de vie 50.000h (rendement 70%).	Lebensdauer 50.000h (Lichtstrom 70%).
Corpo in alluminio anodizzato.	Body in anodized aluminium.	Corps en aluminium anodisé.	Gehäuse in eloxiertem Aluminium.
Cavo in neoprene H05RN-F 3x1mm² di 1,50m.	Neoprene H05RN-F 3x1mm² cable of 1,50m.	Câble en néoprène H05RN-F 3x1mm² de 1,50m.	Neopren-Kabel H05RN-F 3x1mm² von 1,50m.
Alimentatore 220-240V - 50/60Hz incluso.	220-240V - 50/60Hz power supply included.	Alimentation 220-240V - 50/60Hz incluse.	Netzgerät 220-240V - 50/60Hz enthalten.

