
NOBILE ITALIA SpA®



TLM (Bianco-White-Blanc-Weiss)

W

Code 3K	Code 4K	Nominal lumen DOWN 3K	Nominal lumen DOWN 4K	W DOWN	CCT 3K	CCT 4K	mm
T01/S/3K/W_	T01/S/4K/W_	760	800	5,7	3000K	4000K	304
T02/S/3K/W_	T02/S/4K/W_	1520	1600	11,5	3000K	4000K	585
T03/S/3K/W_	T03/S/4K/W_	2280	2400	17	3000K	4000K	865
T04/S/3K/W_	T04/S/4K/W_	3040	3200	23	3000K	4000K	1146
T05/S/3K/W_	T05/S/4K/W_	3800	4000	28,5	3000K	4000K	1426

TLM (Nero-Black-Noir-Schwarz)

B

Code 3K	Code 4K	Nominal lumen DOWN 3K	Nominal lumen DOWN 4K	W DOWN	CCT 3K	CCT 4K	mm
T01/S/3K/B_	T01/S/4K/B_	760	800	5,7	3000K	4000K	304
T02/S/3K/B_	T02/S/4K/B_	1520	1600	11,5	3000K	4000K	585
T03/S/3K/B_	T03/S/4K/B_	2280	2400	17	3000K	4000K	865
T04/S/3K/B_	T04/S/4K/B_	3040	3200	23	3000K	4000K	1146
T05/S/3K/B_	T05/S/4K/B_	3800	4000	28,5	3000K	4000K	1426

CRI >80 | CRI>90 ON REQUEST | DRIVER INCLUDED | W | B | IP20 | CE | F | A++ | A+ | A

Profilo lineare LED per installazione a binario. Kit di fissaggio non inclusi.

LED linear profile for ceiling installation. Fixing kit not included.

Profil linéaire LED pour installation au plafond. Kit de fixation non inclus.

Lineares LED-Profil für Deckenmontage. Befestigungssatz nicht im Lieferumfang enthalten.

LED SAMSUNG 2835 CRI>80 - su richiesta CRI>90 - tolleranza colore 3 MacAdam (3 SDCM).

LED SAMSUNG 2835 CRI>80 - CRI>90 on request - 3 MacAdam Standard Deviation Colour Matching (3 SDMC).

LED SAMSUNG 2835 IRC>80 – sur demande IRC >90 Ellipse 3 Mac Adam (3 SDCM)

LED SAMSUNG 2835 IRC>80 auf Anfrage IRC >90 Ellipse 3 Mac Adam (3 SDCM)

Life time >50.000 h - L80B10 (secondo la potenza). Range potenza e flusso luminoso a Tc 65°C: 5,7-28,5W; 760-4000lm (da 304mm a 1426mm).

Life time >50.000 h - L80B10 (depending on power) Power range and luminous flux at Tc 65°C: 5,7-28,5W; 760-4000lm (from 304mm to 1426mm).

Durée de vie 50.000h – L80B10 (selon la puissance) Puissance et flux lumineux à Tc 65°C 5,7W-28,5W; 760lm-4000lm (de 304mm à 1426mm)

Lebensdauer 50.000h – L80B10 (gemäss Leistung) Leistung und Lichtstrom Tc 65°C 5,7W-28,5W; 760lm-4000lm (von 304mm bis 1426mm)

Profilo di alluminio estruso verniciato bianco o nero. Testate di chiusura in policarbonato bianco o nero.

White or black painted extruded aluminum profile. White or black polycarbonate end caps.

Profil en aluminium extrudé peint blanc ou noir. Embouts de fermeture en polycarbonate blanc ou noir.

Aluminium-Strangpressprofil weiss oder schwarz lackiert. Endkappen in weiss oder schwarz Polykarbonat.

Diffusore opale.

Opal diffuser.

Diffuseur opale.


Diffusor Opal.

Alimentatore 220-240V - 50/60Hz incluso. (ON-OFF, DIM 1-10V, DALI). Controllo wireless.


220-240V – 50/60Hz driver included (ON-OFF, DIM 1-10V, DALI). Wireless control.

Alimentation 220-240V – 50/60Hz incluse. (ON-OFF, DIM 1-10V, DALI). Contrôle Wireless.

Netzgerät 220-240V - 50/60Hz enthalten. (ON-OFF, DIM 1-10V, DALI). Drahtlose Steuerung.



766lm - 13W - 59lm/W



S

Opalino
Opal
Opale
Opal


Versioni prodotto disponibili su richiesta – *Product versions available upon request*
Versions du produit disponibles sur demande – *Produktversion auf Anfrage erhältlich*

Code	Descrizione	*Description*	Description	*Beschreibung*
T01/_/__/_1	Solo con driver ON-OFF Made in Italy	*Only with Made in Italy ON-OFF driver*	Seulement avec alimentation ON-OFF Made in Italy	*Nur mit ON-OFF Made in Italy*
T__/_/__/_1	Con driver ON-OFF Made in Italy	*With Made in Italy ON-OFF driver*	Avec alimentation ON-OFF Made in Italy	*Mit ON-OFF Made in Italy*
T__/_/__/_2	Con driver DIM 1-10V Made in Italy	*With Made in Italy DIM 1-10V driver*	Avec alimentation DIM 1-10V Made in Italy	*Mit DIM 1-10V Made in Italy*
T__/_/__/_3	Con driver DALI Made in Italy	*With Made in Italy DALI driver*	Avec alimentation DALI Made in Italy	*Mit DALI Made in Italy*

Nobile Italia Spa
Viale Alexandre Gustave Eiffel, 100 isola P 21-24 - 00148 Roma, Italia - Tel. +39 06 65002524 r.a. - Fax +39 06 65002861 - info@nobile.it
Legal head office: Piazza di Spagna, 62 - 00187 Roma, Italia
Export Sales Department: Via Lavoratori Autobianchi, 1 20832 Desio (MB), Italia - Tel./Fax +39 03 62 17 90 030 - export.dpt@nobile.it

Rev.02 03/2018

NOBILE ITALIA SpA®



TLM (Bianco-White-Blanc-Weiss)

W

Code 3K	Code 4K	Nominal lumen DOWN 3K	Nominal lumen DOWN 4K	W DOWN	CCT 3K	CCT 4K	mm
T01/M/3K/W_	T01/M/4K/W_	760	800	5,7	3000K	4000K	304
T02/M/3K/W_	T02/M/4K/W_	1520	1600	11,5	3000K	4000K	585
T03/M/3K/W_	T03/M/4K/W_	2280	2400	17	3000K	4000K	865
T04/M/3K/W_	T04/M/4K/W_	3040	3200	23	3000K	4000K	1146
T05/M/3K/W_	T05/M/4K/W_	3800	4000	28,5	3000K	4000K	1426

TLM (Nero-Black-Noir-Schwarz)

B

Code 3K	Code 4K	Nominal lumen DOWN 3K	Nominal lumen DOWN 4K	W DOWN	CCT 3K	CCT 4K	mm
T01/M/3K/B_	T01/M/4K/B_	760	800	5,7	3000K	4000K	304
T02/M/3K/B_	T02/M/4K/B_	1520	1600	11,5	3000K	4000K	585
T03/M/3K/B_	T03/M/4K/B_	2280	2400	17	3000K	4000K	865
T04/M/3K/B_	T04/M/4K/B_	3040	3200	23	3000K	4000K	1146
T05/M/3K/B_	T05/M/4K/B_	3800	4000	28,5	3000K	4000K	1426

CRI >80 | CRI>90 ON REQUEST | DRIVER INCLUDED | W | B | IP20 | CE | F | A++ | A+ | A

Profilo lineare LED per installazione a binario. Kit di fissaggio non inclusi.

LED linear profile for ceiling installation. Fixing kit not included.

Profil linéaire LED pour installation au plafond. Kit de fixation non inclus.

Lineares LED-Profil für Deckenmontage. Befestigungssatz nicht im Lieferumfang enthalten.

LED SAMSUNG 2835 CRI>80 - su richiesta CRI>90 - tolleranza colore 3 MacAdam (3 SDCM).

LED SAMSUNG 2835 CRI>80 - CRI>90 on request - 3 MacAdam Standard Deviation Colour Matching (3 SDMC).

LED SAMSUNG 2835 IRC>80 – sur demande IRC >90 Ellipse 3 Mac Adam (3 SDCM)

LED SAMSUNG 2835 IRC>80 auf Anfrage IRC >90 Ellipse 3 Mac Adam (3 SDCM)

Life time >50.000 h - L80B10 (secondo la potenza). Range potenza e flusso luminoso a Tc 65°C: 5,7-28,5W; 760-4000lm (da 304mm a 1426mm).

Life time >50.000 h - L80B10 (depending on power) Power range and luminous flux at Tc 65°C: 5,7-28,5W; 760-4000lm (from 304mm to 1426mm).

Durée de vie 50.000h – L80B10 (selon la puissance) Puissance et flux lumineux à Tc 65°C 5,7W-28,5W; 760lm-4000lm (de 304mm à 1426mm)

Lebensdauer 50.000h – L80B10 (gemäss Leistung) Leistung und Lichtstrom Tc 65°C 5,7W-28,5W; 760lm-4000lm (von 304mm bis 1426mm)

Profilo di alluminio estruso verniciato bianco o nero. Testate di chiusura in policarbonato bianco o nero.

White or black painted extruded aluminum profile. White or black polycarbonate end caps.

Profil en aluminium extrudé peint blanc ou noir. Embouts de fermeture en polycarbonate blanc ou noir.

Aluminium-Strangpressprofil weiss oder schwarz lackiert. Endkappen in weiss oder schwarz Polykarbonat.

Diffusore microprismatico.

Micro prismatic diffuser.

Diffuseur micro-prismatique.


Diffusor mikroprismatisch.

Alimentatore 220-240V - 50/60Hz incluso. (ON-OFF, DIM 1-10V, DALI). Controllo wireless.


220-240V – 50/60Hz driver included (ON-OFF, DIM 1-10V, DALI). Wireless control.

Alimentation 220-240V – 50/60Hz incluse. (ON-OFF, DIM 1-10V, DALI). Contrôle Wireless.

Netzgerät 220-240V - 50/60Hz enthalten. (ON-OFF, DIM 1-10V, DALI). Drahtlose Steuerung.



1052lm - 13W - 81lm/W



M

Microprismatico
Micro prismatic
Micro-prismatique
Mikroprismatisch


Versioni prodotto disponibili su richiesta – *Product versions available upon request*
Versions du produit disponibles sur demande – *Produktversion auf Anfrage erhältlich*

Code	Descrizione	*Description*	Description	*Beschreibung*
T01/_/__/_1	Solo con driver ON-OFF Made in Italy	*Only with Made in Italy ON-OFF driver*	Seulement avec alimentation ON-OFF Made in Italy	*Nur mit ON-OFF Made in Italy*
T__/_/__/_1	Con driver ON-OFF Made in Italy	*With Made in Italy ON-OFF driver*	Avec alimentation ON-OFF Made in Italy	*Mit ON-OFF Made in Italy*
T__/_/__/_2	Con driver DIM 1-10V Made in Italy	*With Made in Italy DIM 1-10V driver*	Avec alimentation DIM 1-10V Made in Italy	*Mit DIM 1-10V Made in Italy*
T__/_/__/_3	Con driver DALI Made in Italy	*With Made in Italy DALI driver*	Avec alimentation DALI Made in Italy	*Mit DALI Made in Italy*

Nobile Italia Spa
Viale Alexandre Gustave Eiffel, 100 isola P 21-24 - 00148 Roma, Italia - Tel. +39 06 65002524 r.a. - Fax +39 06 65002861 - info@nobile.it
Legal head office: Piazza di Spagna, 62 - 00187 Roma, Italia
Export Sales Department: Via Lavoratori Autobianchi, 1 20832 Desio (MB), Italia - Tel./Fax +39 03 62 17 90 030 - export.dpt@nobile.it

Rev.02 03/2018

NOBILE ITALIA SpA®



TLM (Bianco-White-Blanc-Weiss)

W

Code 3K	Code 4K	Nominal lumen DOWN 3K	Nominal lumen DOWN 4K	W DOWN	CCT 3K	CCT 4K	mm
T01/U/3K/W_	T01/U/4K/W_	570	600	3,8	3000K	4000K	304
T02/U/3K/W_	T02/U/4K/W_	1140	1200	7,5	3000K	4000K	585
T03/U/3K/W_	T03/U/4K/W_	1710	1800	11,5	3000K	4000K	865
T04/U/3K/W_	T04/U/4K/W_	2280	2400	15	3000K	4000K	1146
T05/U/3K/W_	T05/U/4K/W_	2850	3000	19	3000K	4000K	1426


TLM (Nero-Black-Noir-Schwarz)

B


Code 3K	Code 4K	Nominal lumen DOWN 3K	Nominal lumen DOWN 4K	W DOWN	CCT 3K	CCT 4K	mm
T01/U/3K/B_	T01/U/4K/B_	570	600	4	3000K	4000K	304
T02/U/3K/B_	T02/U/4K/B_	1140	1200	7,5	3000K	4000K	585
T03/U/3K/B_	T03/U/4K/B_	1710	1800	11,5	3000K	4000K	865
T04/U/3K/B_	T04/U/4K/B_	2280	2400	15	3000K	4000K	1146
T05/U/3K/B_	T05/U/4K/B_	2850	3000	19	3000K	4000K	1426

CRI >80 | CRI>90 ON REQUEST | DRIVER INCLUDED | W | B | IP20 | CE | F | A++ | A+ | A

Profilo lineare LED per installazione a binario. Kit di fissaggio non inclusi.	*LED linear profile for ceiling installation. Fixing kit not included.*	Profil linéaire LED pour installation au plafond. Kit de fixation non inclus.	*Lineares LED-Profil für Deckenmontage. Befestigungssatz nicht im Lieferumfang enthalten.*
LED SAMSUNG 2835 CRI>80 - su richiesta CRI>90 - tolleranza colore 3 MacAdam (3 SDCM).	*LED SAMSUNG 2835 CRI>80 - CRI>90 on request - 3 MacAdam Standard Deviation Colour Matching (3 SDMC).*	LED SAMSUNG 2835 IRC>80 – sur demande IRC >90 Ellipse 3 Mac Adam (3 SDCM)	*LED SAMSUNG 2835 IRC>80 auf Anfrage IRC >90 Ellipse 3 Mac Adam (3 SDCM)*
Life time >50.000 h - L80B10 (secondo la potenza). Range potenza e flusso luminoso a Tc 65°C: 5,7-28,5W; 760-4000lm (da 304mm a 1426mm).	*Life time >50.000 h - L80B10 (depending on power) Power range and luminous flux at Tc 65°C: 5,7-28,5W; 760-4000lm (from 304mm to 1426mm).*	Durée de vie 50.000h – L80B10 (selon la puissance) Puissance et flux lumineux à Tc 65°C 5,7W-28,5W; 760lm-4000lm (de 304mm à 1426mm)	*Lebensdauer 50.000h – L80B10 (gemäss Leistung) Leistung und Lichtstrom Tc 65°C 5,7W-28,5W; 760lm-4000lm (von 304mm bis 1426mm)*
Profilo di alluminio estruso verniciato bianco o nero. Testate di chiusura in policarbonato bianco o nero.	*White or black painted extruded aluminum profile. White or black polycarbonate end caps.*	Profil en aluminium extrudé peint blanc ou noir. Embouts de fermeture en polycarbonate blanc ou noir.	*Aluminium-Strangpressprofil weiss oder schwarz lackiert. Endkappen in weiss oder schwarz Polykarbonat.*
Sistema ottico UGR<19	*Optical system granting UGR<19*	Optique UGR<19	*Optik UGR< 19*
Alimentatore 220-240V - 50/60Hz incluso. (ON-OFF, DIM 1-10V, DALI). Controllo wireless.	*220-240V – 50/60Hz driver included (ON-OFF, DIM 1-10V, DALI). Wireless control.*	Alimentation 220-240V – 50/60Hz incluse. (ON-OFF, DIM 1-10V, DALI). Contrôle Wireless.	*Netzgerät 220-240V - 50/60Hz enthalten. (ON-OFF, DIM 1-10V, DALI). Drahtlose Steuerung.*



1048lm - 10W - 105lm/W



U

Ottica UGR<19
UGR<19 Optics
Optique UGR<19
Optik UGR<19

Versioni prodotto disponibili su richiesta – *Product versions available upon request*
Versions du produit disponibles sur demande – *Produktversion auf Anfrage erhältlich*

Code	Descrizione	*Description*	Description	*Beschreibung*
T01/_/__/_1	Solo con driver ON-OFF Made in Italy	*Only with Made in Italy ON-OFF driver*	Seulement avec alimentation ON-OFF Made in Italy	*Nur mit ON-OFF Made in Italy*
T__/_/__/_1	Con driver ON-OFF Made in Italy	*With Made in Italy ON-OFF driver*	Avec alimentation ON-OFF Made in Italy	*Mit ON-OFF Made in Italy*
T__/_/__/_2	Con driver DIM 1-10V Made in Italy	*With Made in Italy DIM 1-10V driver*	Avec alimentation DIM 1-10V Made in Italy	*Mit DIM 1-10V Made in Italy*
T__/_/__/_3	Con driver DALI Made in Italy	*With Made in Italy DALI driver*	Avec alimentation DALI Made in Italy	*Mit DALI Made in Italy*

Nobile Italia Spa
Viale Alexandre Gustave Eiffel, 100 isola P 21-24 - 00148 Roma, Italia - Tel. +39 06 65002524 r.a. - Fax +39 06 65002861 - info@nobile.it
Legal head office: Piazza di Spagna, 62 - 00187 Roma, Italia
Export Sales Department: Via Lavoratori Autobianchi, 1 20832 Desio (MB), Italia - Tel./Fax +39 03 62 17 90 030 - export.dpt@nobile.it

Rev.02 03/2018